

SR133.

SR133. 10 ?PK
 k ,... / k Ő ,3 #
 ,... / T | / ,... T ,...3 #
 ! k SQ@+Rwnc A
 k QANĠ



SQ@ S
 0... k ? f
 1,3 RDR+JAB
 ,74 MJCB
 Rwnc+A !SQ@ !
 QANĠ

	0	3mΩ	1μΩ	± 0.5%rdg. ± 5dgt	150mA	1kHz ± 30Hz
	1	30mΩ	10μΩ		150mA	
	2	300mΩ	100μΩ		15mA	
	3	3Ω	1mΩ		1.5mA	
	4	30Ω	10mΩ		150μA	
	0	10V	100μV	± 0.05%rdg. ± 5dgt		/
	1	100V	100mV			
		3.5	LCD	+0.96	OLED	
		1 /				
		/	/	PASS FAIL		
		ABS		PER	SEQ	
		U				

	SR133 .		
	Type-C ()/USB DEVICE (/		
	SCPI		
	<5		
	5	20%	
	5VA		
	7.4V 2000mAh		9VDC 2A
	28	18	0.1*

	0.84kg							
(W × H × D)	114.5 × 251.9 × 85.3(mm)							
	× 1	UT-L82	× 1	-Type-C × 1	&	&	× 1	× 1
	UT-L81		UT-L80					
	2							
	3.40kg							

